

## APPLICATION GUIDE: SMART BLACKBOARD PAINT

*Smart Blackboard Paint is suitable for use on plaster, wallboards, wood, metal and concrete.  
Each tin covers up to 4 s.q.metres/ 43 s.q. feet (based on 2 coats). For interior use only.*

### 1. Preparation

- All surfaces should be clean, dry and free from loose and flaking materials before painting
- Measure the area you wish to paint and clearly mark it using masking tape
- Prime bare and untreated surfaces with a suitable water-based primer such as Smart White Primer
- Once primed, lightly sand the surface

### 2. Application

- Stir paint thoroughly before use
- For best results, apply paint using a foam roller
- Paint the surface using light even strokes, covering 1 metre sections at a time
- Apply 2 coats waiting 3-4 hours between each coat

### 3. Drying Time

- Smart Blackboard Paint will be touch-dry in 1 hour and usable after 4 hours

### 4. Preparation for Use

- Before writing on the surface for the first time, condition the surface by rubbing the side of a stick of chalk all over the surface and erasing immediately with a dry cloth or eraser

### 5. Ongoing Cleaning

- Your blackboard surface can be cleaned with standard blackboard erasers
- A chalky residue will remain when cleaning with a dry cloth or eraser. This can be removed by using a damp cloth
- Wait 7 days after application before using a damp cloth to clean the surface

### 6. Safety

- In case of contact with skin, rinse skin with warm soapy water
- In case of contact with eyes, thoroughly rinse with clean water and seek medical advice
- Keep out of reach of children
- Ensure room is adequately ventilated during application and drying
- For detailed safety information, consult MSDS

**email: [support@smartersurfaces.com](mailto:support@smartersurfaces.com)**

**[www.smartersurfaces.com](http://www.smartersurfaces.com)**

**International customer support: +353 1 4845 627**

