

# Smarter Surfaces<sup>TM</sup>

## Smarter Surfaces Projector Paint: Non-Dry Erase APPLICATION INSTRUCTIONS

### SUITABILITY

*Smarter Surfaces Projector Paint is designed to be used with projection equipment. It is not a dry-erase paint. If you need dry-erase properties, see the full Smarter Surfaces range of products.*

Smarter Projector Paint is suitable for use on plaster, wallboards, wood, metal and concrete. For interior use only.

### 1. Preparation

- All surfaces to be painted should be clean, dry and free from loose and flaking materials.
- Prime bare, untreated surfaces with a suitable primer such as Smart White Primer.

### 2. Application

- Apply two coats over a primed or previously coated white surface.
- Apply with brush, roller, pad or spray.
- If using a roller, it is recommended to use a roller with a short nap.

### 3. Coverage

- This tin covers up to 6.5 s.q.metres/70 s.q. feet (based on 2 coats).

### 4. Drying Time

- Touch dry in 1-2 hours. Re-coatable in 4-6 hours.

### 5. Cleaning

- Clean equipment with warm soapy water.

### 6. Safety

- In case of contact with skin, rinse skin with warm soapy water.
- In case of contact with eyes, thoroughly rinse with clean water and seek medical advice.
- Keep out of reach of children.
- Ensure room is adequately ventilated during application and drying.
- EU limit Value for this product is 30g/l VOC.
- Contains maximum VOCs of 3g/l.
- For detailed safety information consult MSDS.

**email: [support@smartersurfaces.com](mailto:support@smartersurfaces.com)**

**[www.smartersurfaces.com](http://www.smartersurfaces.com)**

**International customer support: +353 1 4845 627**



Google+

