SmarterSurfaces■ The surface of the surface of

SMART FLOOR PROJECTOR SCREEN PAINT

APPLICATION GUIDE

Smart Floor Projector Screen Paint can be applied over existing floor paint, or onto bare concrete It is possible to make it Anti Slip Floor Paint, by adding a finely aggregate to the paint

SUITABLE FOR APPLICATION

- · Any concrete floor subject to light-medium use.
- \cdot Can also be applied to wood and metal.

Each kit covers an area of 4.5m2 / 48 sq. ft. This will create the following screen sizes:

All products within the Smarter Surfaces Projection Range have a certified gypsum Surface Finish Quality Standard of US 4/EU Q3 guaranteeing a smooth, seamless surface ready for use with a high-quality projector for professional projection results.

HOW TO APPLY SMART FLOOR PROJECTOR SCREEN PAINT



PREPARE THE SURFACE

For new concrete and power floated concrete prepare using an Acid etch solution to For application over an existing floor paint. Remove any flaking or poorly bonded paint using a floor scraper. Gloss paint should be lightly sanded to provide a key. Make sure the surface is clean and dust free



REPAIR

Holes or cracks can be repaired with concrete repair compound and allow to dry



APPLICATION

The surface must be dry and clean

Stir the paint thoroughly.

If you require an Anti Slip Floor Paint, add aggregate to the paint and stir well

Apply using a short pile lint free roller.

Use the roller to work the paint into the surface of bare concrete.

A brush can be used for cutting in around the edges.

Once the first coat is applied wait 10 hours before applying the second coat



LIMITATIONS

Avoid applying in cold (below 15°C) conditions.



CLEANING

Use a pH neutral proprietary floor detergent for cleaning. Ensure the product is diluted and handled as per the manufacturer's instructions.as per the manufacturer's instructions.



DRYING TIME

Smart Floor Projector Screen Paint will be usable after 24 hours.

PRODUCT LIABILITY CLAUSE

The sale of our products is subject to our General Terms and Conditions available on **www.smartersurfaces.com**

SUPPORT



